

Reifen- Bezeichnung	PLY	Durchmesser x Breite	Tragfähigkeit der Reifen frei rollend in kg bei 40 Km/h und folgendem Luftdruck in bar																
			0,8	1,0	1,2	1,4	1,6	1,8	2,0	2,2	2,4	2,6	2,8	3,0	3,2	3,4	3,6	3,8	4,0
10.0 / 75 - 15.3	10 PR	760 x 246	---	---	---	---	---	---	---	---	---	---	---	---	1365	1410	1430	1470	1500
11.5 / 80 - 15.3	8 PR	845 x 290	---	---	---	---	---	---	---	---	1300	1450	1600	1650	---	---	---	---	---
11.5 / 80 - 15.3	10 PR	845 x 290	---	---	---	---	---	---	---	---	---	---	---	1735	1810	1860	1900	---	---
13.0 / 75 - 16	10 PR	900 x 336	---	---	---	---	1290	1370	1460	1550	1620	1700	1750	1850	1950	2030	---	---	---
15.0 / 55 - 17	10 PR	850 x 391	---	---	---	---	1340	1530	1660	1760	1855	1950	---	---	---	---	---	---	---
19.0 / 45 - 17	10 PR	866 x 491	---	---	---	---	1550	1780	1860	2000	2100	2150	2230	2360	---	---	---	---	---
15.0 / 70 - 18	10 PR	990 x 391	---	---	---	---	1680	1780	1910	2030	2150	2220	2300	2400	2500	2640	---	---	---
16.0 / 70 - 20	10 PR	1075 x 454	---	---	---	---	1970	2130	2260	2380	2500	---	---	2870	---	3000	---	---	---
21.0 / 80 - 20	12 PR	1362 x 525	---	---	---	4100	4400	4550	5010	5300	5600	---	---	6360	---	---	---	---	---
400 / 60 - 15.5	8 PR	875 x 405	---	---	1440	1540	1640	1670	1800	---	---	---	---	---	---	---	---	---	---
400 / 60 - 15,5	14 PR	875 x 405	---	---	1440	1540	1640	1670	1800	1900	2000	2050	2135	2250	2360	---	---	---	---
500 / 60 - 15,5	12 PR	994 x 503	---	---	---	---	---	---	---	---	---	---	---	3350	---	---	---	---	---
380 / 55 - 17	138 A8	850 x 391	---	---	---	---	1340	1530	1660	1760	---	---	2360	---	---	---	---	---	---
480 / 45 - 17	146 A8	866 x 491	---	---	---	---	1550	1780	1890	2030	---	---	---	2380	3000	---	---	---	---
385 / 65 - 22,5	18 PR	1070 x 390	---	---	---	---	---	---	---	---	---	---	---	4500 kg bei 6 bar / 40 Km/h					
425 / 65 - 22,5	18 PR	1120 x 425	---	---	---	---	---	---	---	---	---	---	---	5000 kg bei 5 bar / 40 Km/h					
445 / 65 - 22,5	18 PR	1180 x 445	---	---	---	---	---	---	---	---	---	---	---	7000 kg bei 8,50 bar / 40 Km/h					

ND-Reifen- Bezeichnung	PLY	Durchmesser x Breite	Tragfähigkeit der Reifen frei rollend in kg bei 40 Km/h und folgendem Luftdruck in bar																
			0,8	1,0	1,2	1,5	1,6	1,8	2,0	2,2	2,4	2,6	2,8	3,0	3,2	3,4	3,6	3,8	4,0
550 / 45 - 22,5	12 PR	1076x550	---	---	---	3000	3100	3250	3400	3700	---	---	---	---	---	---	---	---	---
550 / 60 - 22,5	12 PR	1230 x 550	---	---	---	2825	3540	3780	4010	---	---	---	---	---	---	---	---	---	---
550 / 60 - 22,5	16 PR	1232 x 548	---	---	---	3415	3660	3800	3900	4150	4455	4665	4875	---	---	---	---	---	---
600 / 50 - 22,5	12 PR	1150 x 601	---	2600	2800	3250	3420	3665	3900	---	---	---	---	---	---	---	---	---	---
600 / 55 - 22,5	12 PR	1230 x 602	---	---	3820	4230	4500	4700	5000	5350	5600	6000	---	---	---	---	---	---	---
600 / 55 - 26,5	12 PR	1333 x 600	2755	3140	3490	3980	4135	4430	4710	---	---	---	---	---	---	---	---	---	---
710 / 45 - 26,5	12 PR	1333 x 700	3325	3790	4210	4805	4990	5200	---	---	---	---	---	---	---	---	---	---	---
700 / 50 - 30,5	12 PR	1500 x 700	3500	3985	4500	5055	5250	5450	---	---	---	---	---	---	---	---	---	---	---
750 / 60 - 30,5	8 PR	1650 x 750	4125	4715	5305	6195	6500	7005	7500	---	---	---	---	---	---	---	---	---	---
800 / 40 - 26,5	12 PR	1350 x 800	3715	4235	4700	5365	---	---	---	---	---	---	---	---	---	---	---	---	---
800 / 45 - 30,5	12 PR	1500 x 800	4040	4605	5100	5840	---	---	---	---	---	---	---	---	---	---	---	---	---
850 / 50 - 30,5	8 PR	1650 x 850	4250	4915	5560	6340	6700	7230	7750	---	---	---	---	---	---	---	---	---	---
23.1 - 26	12 PR	1600 x 590	---	---	---	3000	3100	3300	---	---	---	---	---	---	---	---	---	---	---
28.L - 26	12 PR	1600 x 720	---	---	---	3200	3400	3760	---	---	---	---	---	---	---	---	---	---	---

Radialreifen Reifenbezeichnung	Durchmesser x Breite	Tragfähigkeit der Radial-Reifen frei rollend in kg bei 40 Km/h und folgendem Luftdruck in bar															
		1,0	1,2	1,5	1,6	1,8	2,0	2,2	2,4	2,6	2,8	3,0	3,2	3,4	3,6	3,8	4,4
VR 500 / 50 R 17 Flot. pro	950 x 506	1500	1650	1900	2050	2250	2400	2550	2700	2800	3050	3350	3400	3600	3700	3800	4000
VR 560 / 60 R 22,5 Flot. pro	1240 x 565	2400	2500	3000	3200	3400	3600	3900	4300	4500	4600	5000	5300	5500	5800	6050	4400
M 560 / 60 R 22,5 Cargobib	1251 x 570	2790	3120	3610	3770	4100	4430	4760	5090	5330	5460	5600	5740	---	---	---	---
VR 650 / 50 R22,5 Flot. pro	1240 x 650	2490	2760	2800	3320	3600	3860	4210	4500	4700	5000	5260	5600	5800	6200	6400	6600
M 600 / 55 R 26,5 Cargobib	1348 x 626	3100	3470	4020	4200	4570	4940	5300	5670	5930	6080	6390	---	---	---	---	---
VR 620 / 55 R 26,6 Flot. Pro	1350 x 614	2400	3000	3350	3500	3800	4300	4500	4700	5150	5400	5700	6000	6400	6600	6800	7300
TR 680 / 55 R 26,5 Twin Radial	1400 x 680	3610	3910	4375	4530	4840	5150	5540	5770	6075	6380	6690	7000	---	---	---	---
VR 710 / 50 R 26,5 Flot. pro	1340 x 710	2900	3400	3800	3950	4300	4600	4900	5300	5600	5900	6300	6600	6900	7300	7600	7850
M 710 / 50 R 26,5 Cargobib	1382 x 728	3610	4040	4685	4900	5320	5750	6180	6615	6910	---	---	---	---	---	---	---
M 800 / 45 R 26,5 Cargobib	1395 x 829	3640	4090	4540	4990	5440	5890	6340	6790	7160	---	---	---	---	---	---	---
VR 800 / 40 R 26,5 Flot. pro	1340x800	3300	3600	4200	4400	4600	5000	5400	5700	6100	6400	6700	7200	7500	7800	8300	8600
M 600 / 60 R 30,5 Cargobib	1496 x 639	3490	3910	4525	4730	5150	5560	6070	6390	6680	6850	7020	7200	---	---	---	---
M 650 / 65 R 30,5 Cargobib	1623 x 677	4280	4780	5540	5790	6300	6810	---	---	---	---	8600	---	---	---	---	---
M 710 / 50 R 30,5 Cargobib	1495 x 728	3910	4380	5075	5310	5770	6230	6810	7160	7490	7680	7870	8070	8450	---	---	---
TR 750 / 60 R 30,5 Twin Radial	1675 x 754	4500	5000	5750	6000	6380	6770	7330	---	---	---	9030	---	---	---	---	---
M 750 / 60 R 30,5 Cargobib	1680 x 760	4970	5560	6440	6730	7320	7910	8650	---	---	---	9990	---	---	---	---	---
M 850 / 50 R 30,5 Cargobib	1628 x 861	4620	5190	6045	6330	6910	7480	8200	8620	9080	9430	9780	---	---	---	---	---

Legende

- M = Michelin
- TR = Trelleborg
- VR = Vredestein